

DECLARATION OF PERFORMANCE

DOP: NO. BRD046

(model in accordance with Commission Delegated Regulation (EU) No. 574/2014)

Unique identification code of the product type:	Pandser EPDM ZK-Acryl Art. no.: WKFE555-1005 to WKFE555-1060
Intended use(s):	Self-adhesive vapour control layer for use in buildings, EN 13984, type A
Manufacturer:	Berdal rubber & plastics BV Bedrijvenpark Twente 193 7602 KG Almelo
Authorised representative:	Not applicable
System(s) for assessment and verification of constancy of performance (AVCP):	AVCP 3
Harmonised standard:	EN 13984:2013
Notified body:	

DECLARED PERFORMANCE(S):

Essential characteristics	Performance	Test standard
Reaction to fire	Class E	EN 13501-1
Watertightness	Pass	EN 1928
Water vapour diffusion resistance factor (μ)	70,000	EN 1931
Water vapour diffusion after ageing	Pass	EN 1296 / EN 1931
Resistance to impact [mm]	NPD (No Performance Determined)	EN 12691
Shear strength of joint [N/50 mm]	≥ 45	EN 12317-2
Tensile strength (l, w) [N/mm ²]	≥ 7	EN 12311-2B
Elongation at break (l, w) [%]	≥ 400	EN 12311-2B
Tear resistance (l, w) [N]	≥ 60	EN 12310-1
Alkali resistance	Pass	EN 1847 / EN 12311-2B
Dangerous substances	Pass	

The performance of the product identified above is in conformity with the declared performance(s). This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer



B.M.D. van Kamperdijk, General Manager
In Almelo on 19 July 2024

V:1.0