



PANDSER NAIL SEALING TAPE

GENERAL INFORMATION

Pandser Nail Sealing Tape provides a water-resistant and airtight seal when fixing battens to membranes. Thanks to its polyethylene foam composition, the tape forms a durable intermediate layer that prevents direct contact between the battens and the membrane.

This helps protect the membrane from potential damage caused by acids or chemicals released from (treated) wood. Additionally, the tape ensures a seamless seal around screw and staple holes.

The synthetic rubber adhesive layer allows for quick and easy installation.



AVAILABLE DIMENSIONS

Dimensions	Article Number	EAN-Code
50 mm x 30 m x 3mm	VPM10300-9068	8713331032207

SPECIFICATIONS

Characteristics	Performance	
Material	PE foam	
Colour	Anthracite	
Processing temperature	from 5 °C	
Temperature resistance	-30 °C to +80 °C, storage from 15 - 25 °C with rH 40 - 60	
Rain resistant	Minimum 600 Pa	
Thickness	3 mm	
Width	50 mm	
Length	30 m	
Pieces per box	10	
Cover material	None, with firmly annealed silicone film	
Adhesive	Synthetic rubber	

FEATURES

- High adhesive strength
- Waterproof
- Single-sided self-adhesive
- Can be cut to size

Pandser nail sealing tape is in most cases wider than the counter batten, keeping it clear of the roof membrane. This keeps the counter batten dry and prevents water from penetrating screw or nail perforations.



APPLICATIONS

Pandser nail sealing tape is used for the waterproof sealing of roof membranes on sloping roofs underneath the battens, especially for roof slopes less than 25°.

PROCESSING INSTRUCTIONS

- Ensure the surface is clean and free of dust for good adhesion.
- Do not apply the Pandser nail sealing tape to frozen surfaces, as it will not adhere properly.
- Apply the tape in vertical strips on the roof membrane.
- Then position the counter batten exactly in the middle of the tape, ensuring that the Pandser nail sealing tape remains visible on both sides underneath the counter batten.

ALTERNATIVE NAMES

Also referred to as:

- Counter batten tape
- Batten sealing tape







DISCLAMER

Processing and application of Pandser Nail Sealing Tape must follow the relevant installation guidelines and the manufacturer's instructions. Improper use – such as application on dirty, wet or frozen surfaces – may compromise performance.

Responsibility for correct application lies with the installer. Pandser accepts no liability for damage or defects resulting from incorrect use, unsuitable substrates, or applications outside the described scope. For special applications or in case of doubt, we recommend consulting your supplier in advance.

Versie: Pandser Nail Sealing Taoe 1.0 TDS - EN